

Technical Data Resiblock Resimac

| | |
|----------------------------|--|
| Surface Preparation | <p>Surfaces should be clean, dry and free from dust, dirt, oil, grease, other contamination, and loose particles which might hinder adhesion. If necessary apply a mould cleaner prior to application.</p> <p>Repair cracks and holes as necessary. Ensure repairs are completely dry before painting.</p> <p>Treat oil stains with a proprietary stain remover as necessary.</p> <p>For best results jetwash areas to be treated on a low/medium setting to remove all loose material, moss, algae etc. Allow to dry for 48 hours before application.</p> |
| Cleaning | <p>Clean all equipment immediately after use with clean water.</p> |

| | |
|--------------------------|--|
| Health and Safety | <p>Refer to Manufacturers Health and Safety Data Sheet.</p> |
| Disposal | <p>Do not dispose of into drains, water courses, or where ground or surface water may be affected. Dispose of empty containers in accordance with local authority requirements</p> |

The foregoing information is given in good faith on the basis of practical experience and extensive laboratory tests. Quoted figures are either theoretical values or typical of production batches. However, as we have no control over the conditions of application or the quality and standard of preparation of the substrate and the many other factors affecting the use and application of the product, the customer must determine the suitability of the delivered product for the intended application. Therefore unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of this product or for any loss or damage arising out of the use of the product, or its use in conjunction with other manufacturer's product(s). Stir the paint well before use and always check the shade as no responsibility for a colour complaint is accepted after application. The information in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous improvement. For professional use only

Resimac Tarmac Restorer. March 13.

Resiblock Ltd □ Resiblock House, Archers Fields Close, Basildon, Essex, SS13 1DW