



Sealing, Stabilising, Protecting Paving

Datasheet

RESIBLOCK PORCELAIN AND VITRIFIED PAVING SEALER

Product Description

RESIBLOCK *PORCELAIN AND VITRIFIED PAVING SEALER* is a low viscosity impregnating sealer virtually undetectable following application. It combines unique Nano particle chemistry with Poly Ionic Technology resulting in revolutionary protection. The deep penetrating formulation provides an excellent barrier against dirt detritus and fluid damage. Its unique formulation is UV resistant and will provide long lasting protection even after the initial beading has subsided.

The System

Ideal for use with:-

Porcelain and Vitrified paving
Sandstone
Yorkstone
Limestone
Slate
Travertine
And other forms of natural stone

Limitations of Use

PIC, Engineering Bricks, Quarry Tiles

Application Information

1. Ensure the surface and **joints** are THOROUGHLY DRY and free from dirt and debris.
2. Ensure that RESIBLOCK *PORCELAIN AND VITRIFIED PAVING SEALER* is only applied when there is no risk of rain within the next 8 hours.
3. Do not apply in extremes of temperature (below 3° C or above 30° C). For temperatures outside this range contact Resiblock's Technical Department.
4. Apply to surface using a Resiblock application roller, remove any build up in depressions with a clean roller or builder's sponge.
5. Application rates vary depending on porosity but will be in the order of 4-8m² per litre. A small inconspicuous test area is recommended, view results no earlier than 24 hours after – try a free sample.
6. Avoid walking on the sealed area for 3-6 hours after application and do not drive motor vehicles on the surface for 24 hours.
7. RESIBLOCK *PORCELAIN AND VITRIFIED PAVING SEALER* is NOT a jointing sand stabiliser.
8. ALWAYS WEAR PROTECTIVE GLOVES AND GOGGLES. NO SMOKING. WEAR A MASK WHEN WORKING IN CONFINED AREAS. Please refer to current SDS.
9. All uncured sealant and tools should be cleaned immediately using RESIBLOCK Resiclean – Tool Cleaner.

Features

- Resistant to staining by dirt, debris, and fluids **Guaranteed***
- Virtually undetectable following application
- Manufactured under ISO 9001
- One coat, easy application Resiblock application roller or brush
- High degree of resistance to chemicals
- Non film forming
- Full molecular bonding upon cure
- Lasts up to 5 years
- Repels oil and water-based staining – **Guaranteed***

Health and Safety

PVC gloves and protective clothing/face shield must be worn, plus use of a barrier cream on exposed areas of skin, as uncured RESIBLOCK *PORCELAIN AND VITRIFIED PAVING SEALER* may be considered a hazardous material.

No smoking or naked flames to be allowed, as RESIBLOCK *PORCELAIN AND VITRIFIED PAVING SEALER* is FLAMMABLE. Ensure area to be treated is well ventilated. If public access is allowed, erect NO SMOKING signs and site fire extinguishers.

A mask of the recommended type is **essential** when using a paintbrush, working close to the surface or in a poorly ventilated area. Sabre or Martindale is recommended. Always use a good quality paintbrush.

Do not apply RESIBLOCK *PORCELAIN AND VITRIFIED PAVING SEALER* in the presence of foodstuffs. Once fully cured RESIBLOCK *PORCELAIN AND VITRIFIED PAVING SEALER* can be considered innocuous. Do not clean hands with RESIBLOCK Resiclean – Tool Cleaner as solvents may de-fat skin leading to dermatological problems.

Do not return unused material to original containers. DO NOT RESEAL or store partly used kegs. Material so stored may have poor adhesion, Carbon Dioxide may generate and put the drum under pressure, which might rupture the drum. Furthermore, partial, or total solidification of the sealant may occur.

PLEASE NOTE this data sheet represents an abbreviation only of technical information, particularly as it relates to fields of use, application and health and safety. As such it is essential that the latest copy of our full technical data is consulted prior to application.

General Technical Data

Coverage

4 -8m² per litre

Cleaning of Tools

RESIBLOCK Resiclean-Tool Cleaner

Drying Times

3-6 hrs @ 20°C

Storage

Store under cover and protect from extremes of temperature.
Ensure contents of container are thoroughly mixed.

Flash Point

61° C

Can Sizes

5 litre

Shelf Life

18 months (unopened containers)

Shipping Specification

Packing Group: Not Applicable
UN No: Not Applicable

Resiblock Ltd
Resiblock House
Archers Fields Close
Basildon
Essex
SS13 1DW
United Kingdom
Telephone no: +44 (0)1268 273344
Fax no: +44 (0)1268 273355
Email: technical@resiblock.com
Website: www.resiblock.com



There's Nothing Like It!!