



RESIBLOCK '22' WB

INSTALLATION INFORMATION

On new projects, ensure paving is sealed with RESIBLOCK '22' simultaneously with pavement construction, on a daily basis. DO NOT WAIT until project is complete.

CONTAINER SIZES

RESIBLOCK '22' WB is available in 5, 25 litre containers, 200 litre barrells and 1000 litre intermediate bulk container (IBC)

APPEARANCE

RESIBLOCK '22' WB in the container appears as a low viscosity polyurethane/acrylic hybrid low odour water based urethane having a jointing sand stabiliser. Application will not significantly alter the appearance of concrete pavers other than a slight darkening of the surface having the effect of temporarily enhancing the inherent colours of the pavers. This will ultimately become absorbed giving the appearance of being unsealed.

COVERAGE

Coverage can vary between 1.6-2.4 m² per litre, (on new C.B.P. expect 2.0 m² per litre) depending on type of paver and depth of joint penetration required. In commercial areas which may be subject to a harsh environment or on clay pavers, the lower limit of coverage should be considered. Accurate application rates are essential to achieve full technical benefits. Furthermore material usage can increase by up to 25% on old/worn pavers or specialist blocks with wide joints i.e. angular/rumbled. Please consult our technical department for specific application rates. RESIBLOCK '22' WB being a single pack product, can be used straight from the container without thinning or addition of a reactive agent; it must not be diluted. Agitate before use.

SUBSTRATE/SURFACE CONDITIONS

The surface should also be clean and free from oil, algae, dust and lime bloom. Temperature must be above 5°C and below 45°C. Application outside of these temperature ranges may be possible, but contact our technical department first. Surface should be dry. Jointing sand which contains moisture can prevent bonding and stabilisation of joints. Do not use if rainfall is forecast within 8 hours of project completion.

Trade Tip. If you wish to see if the paving is perfectly dry, simply scrape out the jointing sand to a depth of 25mm; if it is dry, so are the blocks.

Ensure that the sand does not protrude from the top of the joint/base of the chamfers, in accordance with BS 7533, if the sand is not properly removed, joint integrity may be compromised, further it may be picked up by the application tools.

If pavers/joints have been previously treated with any other stabiliser or sealer, please refer to our Technical Department prior to application for advice.

PREPARATION – NEWLY INSTALLED PAVING (Paving installed with 4-6 weeks)

On new work all that is usually required is a good sweep with a stiff broom, however if the surface has become partially weathered or contaminated, wire brush to remove all debris. For large areas pressure cleaning may be more effective. For successful use, optimum performance and maximum penetration of RESIBLOCK '22' WB, ensure joints are well filled to the bottom of the chamfers with clean, compacted kiln-dried sand, complying to BS 7533 or equiv. (See notes on substrate conditions re. sand removal and moisture).

Application to poorly prepared pavers particularly in respect of dampness can result in inadequate joint penetration or paver adhesion, and in exceptional circumstances discoloration and disbonding.

Engineers note. Application specification should note moisture content of the pavers not to exceed 6% and air temperature should be checked to ensure it is within 3°C of the dew point. In an exceptionally dry atmosphere, increase the humidity, e.g. with a water sprinkler, the block paving should then be allowed to dry, leaving sufficient residual moisture to allow polymerisation to take place.

PREPARATION – EXISTING PAVING

This is probably the most essential part, inasmuch as it will determine the technical standard of the finished paved area. The pavers must be thoroughly cleaned using a pressure cleaner to remove all algae and lichen. This operation will also *blast out* all weeds and grass, and most of the top layer of jointing sand (minimum 20mm) from between the blocks. It should also remove all food and drink stains along with any surface dirt and grime.

Note. Occasionally the action of washing or pressure washing will cause substrate saturation and/or reactivate efflorescence. Therefore allow 2 weeks between cleaning and application of RESIBLOCK '22' to allow to dry out and to check for lime-bloom reappearance.

Once the substrate has been allowed to thoroughly dry, the joints between the pavers must be re-filled using kiln dried sand. Top up the joints in accordance with BS 7533.

More detailed information on block/brick cleaning can be found by contacting the Brick Development Assoc. in Berkshire (01344 885651) and obtaining a copy of their publication 'Building Note 2 - Cleaning of Brickwork'.

EQUIPMENT

RESIBLOCK SQUEEGEE.

METHOD OF APPLICATION

Application to concrete or clay pavers can be sealed using this method. An area approximately 1m by 10m should be marked out and the contents of a 5 litre container (gauging pot e.g. 5 litre watering can with rose attached) evenly poured out over the designated area. This should be immediately spread out and wiped from the surface and into the paver joints using a RESIBLOCK SQUEEGEE. Sufficient material should be worked into the joints so it will initially **fill the chamfers** (ultimately to be completely absorbed). Surplus RESIBLOCK '22' WB must not remain on the paver surface but squeegeed into the joints as described; this is **CRITICAL ON CLAY PAVERS**. For further information refer to Resiblock '22' WB pictorial application summary.

TWO-COAT APPLICATION

A second coat is not normally recommended unless it is required to render the surface impervious to chemical or hydrocarbon spillages. Contact Resiblock Technical Department for further assistance.

NOTE. Clay pavers must only have 1 coat.

ANTI-SLIP SURFACES

In most cases RESIBLOCK '22' WB should not adversely affect the SRV (grip characteristics) of the pavers. But on higher density pavers, gradients, SSF's (around fuel pumps), or specialist area (airfields, equestrian facilities, wheelchair access points) and particularly when used as a two coat system, additional anti-slip qualities may be required. Contact Resiblock Technical Department for further assistance.

CURING PERIOD

Rapid initial cure will take place depending on ambient temperature, humidity and block porosity; 1-3 hours can be expected. Immediately the surface is dry the paved area can be subjected to foot or light traffic but full chemical cure must be allowed to take place (24 hours) before being subjected to full traffic use.

STORAGE

Store under cover and protect from extremes of temperature.

SHELF LIFE

RESIBLOCK '22' *WB*, (unopened containers), has a shelf life of 12 months. For further information refer to product datasheet.

CLEANING TOOLS AND EQUIPMENT

All uncured Resiblock '22' *WB* should be cleaned immediately using warm water and good quality detergent.

HEALTH AND SAFETY GUIDELINES

PVC gloves and protective clothing/face shield must be worn, plus use of a barrier cream on exposed areas of skin, as uncured RESIBLOCK '22' *WB* may be considered a non-hazardous material.

Do not apply RESIBLOCK '22' *WB* in the presence of foodstuffs. Once fully cured RESIBLOCK '22' *WB* can be considered innocuous.

Do not return unused material to original containers. DO NOT RESEAL or store partly used kegs. Material so stored may have poor adhesion and Carbon Dioxide may generate and put the drum under pressure, which might rupture the drum. Furthermore partial or total solidification of the sealant may occur.

Please refer to Resiblock Limited's current Material Data Sheets for the latest and comprehensive information on this section.

LIMITATIONS

RESIBLOCK '22' *WB* is ***not suitable*** for pattern imprinted concrete, engineering bricks, quarry tiles, marble, granite, exposed aggregate panels etc. Contact our technical department for more information. RESIBLOCK '22' *WB* will resist slabs from fading, by eventually darkening, however lighter coloured paving units (inc. buff/grey) may become dark yellow/brown (particularly if over applied). Always trial/apply to a small inconspicuous area in the first instance in order to assess suitability.

Since its inception in 1993 Resiblock Ltd have been dedicated to providing solutions for stabilising and protecting small element flexibly laid paving for more than 30 years.

From Portland Oregon, USA to Christchurch, New Zealand and almost everywhere in between, Resiblock – the world’s favourite paving sealer! At Resiblock we believe that our products have been used in more countries around the world than any other paving sealer! Utilised at port pavements, aircraft pavements, theme parks, patios and driveways, we have provided sealing solutions for literally millions of square metres! Resiblock’s expertise and knowledge generally being regarded as the most definitive in its field.

www.resiblock.com
technical@resiblock.com

RESIBLOCK '22' WB

APPLICATION GUIDE SUMMARY*

On new projects, ensure paving is sealed with RESIBLOCK '22' WB simultaneously with pavement construction, on a daily basis. DO NOT WAIT until project is complete.

1. Make sure the surface and **jointing sand** are THOROUGHLY DRY and free from dirt.
2. Ensure that RESIBLOCK '22' WB is only applied when there is no risk of rain within the next 8 hours.
3. Do not apply in extremes of temperature (below 5°C or above 45°C).
4. Ensure paving is thoroughly swept and that no jointing sand remains in the chamfers of the pavers.
5. Apply to surface using a watering can (with the rose) and remove all surplus with the SQUEEGEE.
6. Accurate application rates are critical to ensure full joint stabilisation (typically 1 litre/2m²). 200 x 100 CBP
7. A MINIMUM of 3 hours and a MAXIMUM of 24 hours between the first and second coats. Two coats are recommended to prevent fuel/water infiltration. ONE COAT ONLY on clay pavers.
8. Avoid walking on the sealed area for 3 hours after application and do not drive motor vehicles on the surface for 24 hours.
9. ALWAYS WEAR PROTECTIVE GLOVES AND GOGGLES. WEAR A MASK WHEN WORKING IN CONFINED AREAS. Please refer to current SDS.
10. All uncured spillage's/splashes, and all tools must be cleaned immediately with Resiblock NS Cleaner.

**FOR FREE ADVICE TELEPHONE
RESIBLOCK
01268 273344**

* *This fact sheet is not intended to replace the full application instructions, which must be read prior to application*

Whilst Resiblock Limited believe that the data contained herein is factual, the opinions expressed are those of experts (qualified or otherwise) regarding the results of tests. The data is not to be taken as a warranty or representation for which Resiblock Limited assumes legal responsibility. This data is offered solely for your consideration, investigation and verification. Any use of this data must be determined by the user to be according to the applicable laws and regulations.

Resiblock Limited try to ensure any advice, recommendations or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our products are used, hence our advice does not release **end-users from the obligation to satisfy themselves by prior testing that the product/s is suitable for their specific application, and that the actual conditions of use are suitable.**

Accordingly no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors. Each end-user should always ensure that they have consulted our latest publications and that the relevant information concerning this material is communicated to all members of their organisation handling our products.

Resiblock Limited's liability is for replacement of material proved to be defective only. Products are sold subject to our Standard Conditions of Sale.

The Company's policy of continuous product development and improvement renders specifications liable to modifications. Information provided in this literature is therefore subject to change without prior notification.

This entire document is copyright protected. All rights reserved. First published in Great Britain 1993. No part of this publication may be produced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording and/or otherwise without prior written permission of the publishers.

© Resiblock Limited 1993
09/03/2009